



Key features

Series	18KF
Dimension	Ø 18 x 81.5 mm
Interface	PNP Normally open (NO) PNP Normally closed (NC)
Principle of operation	Photoelectric sensor
Principle of optical operation	Through-beam sensor (receiver)
Light type	Laser Red light
Range	0...60 m
Connection	Connector, M12x1-Male, 4-pin
Housing material	PBT
Material sensing surface	PMMA
Operating voltage Ub	10...30 VDC
Approval/Conformity	CE UKCA cULus WEEE
Trademark	Global

Key features

Series	18KF
Dimension	Ø 18 x 81.5 mm
Interface	PNP Normally open (NO) PNP Normally closed (NC)
Principle of operation	Photoelectric sensor
Principle of optical operation	Through-beam sensor (receiver)
Light type	Laser Red light
Range	0...60 m
Connection	Connector, M12x1-Male, 4-pin
Housing material	PBT
Material sensing surface	PMMA
Operating voltage Ub	10...30 VDC
Approval/Conformity	CE UKCA cULus WEEE
Trademark	Global

Key features

Series	18KF
Dimension	Ø 18 x 81.5 mm
Interface	PNP Normally open (NO) PNP Normally closed (NC)
Principle of operation	Photoelectric sensor
Principle of optical operation	Through-beam sensor (receiver)
Light type	Laser Red light
Range	0...60 m
Connection	Connector, M12x1-Male, 4-pin
Housing material	PBT
Material sensing surface	PMMA
Operating voltage Ub	10...30 VDC
Approval/Conformity	CE UKCA cULus WEEE
Trademark	Global